


7	压柄	SUS	
6	触点	银合金	
5	端子	C2680	镀银
4	弹片	C5210	
3	按钮	PBT	白色
2	上盖	PBT	黑色
1	底座	PBT	白色
序号	名称	材料	备注



Rating	DC30V 100mA	Electrical Life	1000,000 cycles
Contact Resistance	500m Ω Max	Mechanical Life	1000,000 cycles
Insulation Resistance	>100MΩ DC500V	Ambient Temper. Used	-25℃ to +85℃
Withstand Voltage	AC500V 1min.	Ambient Humidity Used	≤85% at +40℃
Soldering Temper.	235±5℃ 5s	Operating Force	20±15gf max

							DSND		DATE		SCALE: N/A	MODEL TYPE: MICRO SWITCH			
					ANGULAR	±5°	DWN		DATE		VIEW: 	PART NO.:			
Δx					L≤4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: DM1-135P-1-16			
Δx					4<L≤16	±0.3									
Δx					16<L≤63	±0.4									
MARK	DESCRIPTION		DATE	REVISED	APPROVED	L>63	±0.5	APPD		DATE		SIZE: A4			
REVISIONS							UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn													1.0g	1/1	A0