

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

UL Standard

- 1.Rated voltage/current : 300V / 20A
- 2.Torque value : M2.5 , 3.54Lb.in
- 3.Wire range : 30~12AWG

IEC Standard

- 1.Rated voltage/current : 250V / 18A
- 2.Torque value : M2.5 , 0.4N·m
- 3.Wire range : 2.5mm²

NOTES2:





- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 5.0mm, Poles : N=02~XXP
- 3.Stripping length : 6~7mm
- 4.Withstanding voltage : AC2000V/1Min
- 5.Operating temperature: -40°C~+105°C
- 6.Undimensioned tolerances:

Pitch range in mm		Nominal dimension range in mm						—	∩	∇
To	Over	To	Over	To	Over	To	Over			
6	6	10	10	30	30	60	60	100	100	150
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2*	0.1/10	<

7.RoHS Compliance

DB128V - 5.08 - XXP - COLOUR

(Series No.) (Pitch) (Poles)

(Color):1.(Grey)2.(Blue)3.(Black)4.(Green)5.(Orange)
6.(Red)7.(Transparent)8.(Yellow)9.(White)

DETACHED LISTS	PART NO.:	/	DORABO 慈溪市地博电子有限公司 CIXI DORABO ELECTRONICS CO.,LTD				
	APPD:	/	NAME: DB128V-5.08-XXP-COLOUR				
	CHKD:	/					
	DRFT:	/	TITLE: CUSTOMER DRAWING			REV	DO
	 THIRD ANGLE PROJECTION		DRAWING NO.: /			SHEET	1/1
			DO NOT SCALE DRAWING	SCALE	1:1		