



|    |               |
|----|---------------|
| 编号 | SCTF2020HQ112 |
| 日期 | 2022/8/10     |
| 版本 | B01           |

# 承 认 书

## SPECIFICATION FOR APPROVAL

|                       |                        |
|-----------------------|------------------------|
| 客户名称 Customer Name:   | 华秋商城                   |
| 供应商物料名称 Part Name:    | 石英晶体振荡器                |
| 产品描述 Description:     | SMD7050 32.768KHz/3.3V |
| 供应商物料料号 Part NO.:     | S7D32.768KB20F30T      |
| 供应商名称 Supplier Name : | 深圳市星通时频电子有限公司          |

PLEASE CONFIRM OUR SPECIFICATION. 敬请确认规格书之内容。

| CUSTOMER APPROVAL 客户审批     |     |     |
|----------------------------|-----|-----|
| 物料代号 PART NO. _____        |     |     |
| 使用于机型 USED IN MODEL: _____ |     |     |
| 工程部                        | 品质部 | 采购部 |
|                            |     |     |

(敬请确认后返回一份, 谢谢!)

| SUPPLIER APPROVAL 供应商审批 |         |             |
|-------------------------|---------|-------------|
| DGN.制表人                 | CKD. 校对 | APPD. 审核、签章 |
| 吴丽红                     | 李良      | 胡华才         |

地址: 深圳市南山区龙珠四路方大城T2栋10楼

Add: 10 / F, Building T2, Fangdacheng, Longzhu 4th Road, Nanshan District, Shenzhen, China.

Website: www.sctf-crystal.com

Email: info@sctf-crystal.com

TEL: 0755-86097430

FAX: 0755-86097259

Page: 1




# ■ Electrical Specification 电气参数

| N0. | Item                                   | Electrical Spec. | Notes                                                                                                                                    |
|-----|----------------------------------------|------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | Holder Type<br>封装                      | SMD7050          |                                                                                                                                          |
| 2   | Nominal Frequency<br>标称频率              | 32.768K Hz       |                                                                                                                                          |
| 3   | Frequency stability<br>常温频差            | ±20PPM           | at 25℃±2℃                                                                                                                                |
| 4   | Temperature Drift<br>温度频差              | ±30PPM           | at -40~85℃                                                                                                                               |
| 5   | Operating voltage<br>工作电压              | 3.3V             | ±10% max.                                                                                                                                |
| 6   | Output<br>输出模式                         | CMOS             |                                                                                                                                          |
| 7   | Output load condition<br>负载            | 15pF             |                                                                                                                                          |
| 8   | Current consumption<br>消耗电流            | 90 uA max.       |                                                                                                                                          |
| 9   | Operating temperature range<br>工作温度范围  | -40~85℃          |                                                                                                                                          |
| 10  | Storage Temperature Range<br>存储温度范围    | -55~125℃         |                                                                                                                                          |
| 11  | Duty Cycle<br>占空比                      | 45%-55%          |                                                                                                                                          |
| 12  | Rise / Fall Time<br>上升/下降沿时间           | 25 nS max.       |                                                                                                                                          |
| 13  | High output voltage<br>高电平             | 0.9Vdd min.      |                                                                                                                                          |
| 14  | Low output voltage<br>低电平              | 0.1Vdd max.      |                                                                                                                                          |
| 15  | Start-up Time<br>起振时间                  | 5mS max.         | To 90% of Final Amplitude                                                                                                                |
| 16  | Enable Voltage High (Logic 1)<br>使能高电平 | 70%Vdd min.      | Output will be enable if OE is Logic 1 or open ;<br>Output will be disable if OE is Logic 0.<br>输出使能OE是高电平1或者悬空，频率输出；输出使能OE是低电平0，则无频率输出。 |
| 17  | Enable Voltage Low (Logic 0)<br>使能低电平  | 30%Vdd max.      |                                                                                                                                          |
| 18  | Enable Delay Time<br>使能延迟              | 2 mS max.        |                                                                                                                                          |
| 19  | Aging<br>老化                            | ±3ppm            | 1st. Year at 25℃                                                                                                                         |

SHENZHEN SCTF ELECTRONICS CO. , LTD

| DATE      | Specification of quartz crystal oscillator<br>石英晶体振荡器规格书 | Page: |
|-----------|----------------------------------------------------------|-------|
| 2022/8/10 | P/N: S7D32.768KB20F30T<br>Spec.NO.: SCTF2020HQ112        | 3     |



## ■ DIMENSIONS 产品尺寸



Units (单位): mm(毫米)


Pad Functions:

1. ENABLE CONTROL
2. GND
3. OUT PUT
4. VDD



suggested solder pad layout

## ■ TESTING CIRCUIT 测试电路



※ Notes: PIN 1 connected to Vdd or floating, the product is working properly; connected to GND, stops working.


| SHENZHEN SCTF ELECTRONICS CO. , LTD |                                                          |       |
|-------------------------------------|----------------------------------------------------------|-------|
| DATE                                | Specification of quartz crystal oscillator<br>石英晶体振荡器规格书 | Page: |
| 2022/8/10                           | P/N: S7D32.768KB20F30T<br>Spec.NO.: SCTF2020HQ112        | 4     |

## ■ WAVEFORM CONDITIONS 输出波形




Waveform measurement system should have a min. bandwidth of 5 times the frequency being tested.

## ■ Product Structure




## ■ Marking



| SHENZHEN SCTF ELECTRONICS CO. , LTD |                                                          |       |
|-------------------------------------|----------------------------------------------------------|-------|
| DATE                                | Specification of quartz crystal oscillator<br>石英晶体振荡器规格书 | Page: |
| 2022/8/10                           | P/N: S7D32.768KB20F30T<br>Spec.NO.: SCTF2020HQ112        | 5     |

## REFLOW PROFILES 回流焊条件

| Profile Feature                                                        | Sn-Pb Eutectic Assembly | Pb-Free Assembly |
|------------------------------------------------------------------------|-------------------------|------------------|
| Preheat/Soak                                                           |                         |                  |
| ●Temperature Min( $T_s$ min)                                           | 100 °C                  | 150 °C           |
| ●Temperature Max ( $T_s$ max)                                          | 150 °C                  | 200 °C           |
| ●Time ( $T_s$ min to $T_s$ max)                                        | 60-120 seconds          | 60-120 seconds   |
| Ramp-up rate ( $T_L$ to $T_p$ )                                        | 3 °C/second max.        | 3 °C/second max. |
| Time maintained above                                                  |                         |                  |
| ●Liquidous temperature ( $T_L$ )                                       | 183 °C                  | 217 °C           |
| ●Time ( $t_L$ ) maintained above $T_L$                                 | 60-150 seconds          | 60-150 seconds   |
| Peak package body temperature ( $T_p$ )                                | 235 °C                  | 260 °C           |
| Time within 5 °C of the specified classification temperature ( $T_p$ ) | 20 seconds              | 30 seconds       |
| Ramp-down rate ( $T_p$ to $T_L$ )                                      | 6 °C/second max.        | 6 °C/second max. |
| Time 25 °C to peak temperature                                         | 6 minutes max.          | 8 minutes max.   |
| Suggest reflow times                                                   | 3 Times max.            |                  |



SHENZHEN SCTF ELECTRONICS CO. , LTD

|           |                                                          |       |
|-----------|----------------------------------------------------------|-------|
| DATE      | Specification of quartz crystal oscillator<br>石英晶体振荡器规格书 | Page: |
| 2022/8/10 | P/N: S7D32.768KB20F30T<br>Spec.NO.: SCTF2020HQ112        | 6     |

## ■ RELIABILITY SPECIFICATION可靠性参数


| 序号<br>NO. | 项目<br>ITEM                | 条件<br>CONDITIONS                                                                                                                                                                                                                                                             | 合格标准<br>BASIS OF VERDICT                                    |
|-----------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| 1         | 跌落<br>DROP                | 100cm高处自由跌落到3cm厚木板上,3次<br>High:100cm;Thickness:3cm;3 times.                                                                                                                                                                                                                  | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 2         | 振动<br>VIBRATION           | 频率 Frequency:10~57.7Hz;幅度 Amplitude: $\pm 0.75 \text{mm}$<br>频率Frequency:57.7Hz~500Hz;加速度幅度acceleration rate:98m/s <sup>2</sup><br>周期 Cycle time:10-500-10Hz: 15min<br>振动方向 Direction:X,Y, Z<br>振动时间 Duration: 每个方向2小时 2 h/direction.                                        | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 3         | 温度变化<br>TEMPERATURE SHOCK | -40℃ $\pm 2^\circ\text{C}$ (30min) $\longleftrightarrow$ 85℃ $\pm 2^\circ\text{C}$ (30min);循环10次<br>-40℃ $\pm 2^\circ\text{C}$ (30min) $\longleftrightarrow$ 85℃ $\pm 2^\circ\text{C}$ (30min);For 10 cycles                                                                 | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 4         | 湿热<br>HUMIDITY            | 温度:40℃ $\pm 2^\circ\text{C}$ ;湿度90-95%;时间:96小时<br>Temp:40℃ $\pm 2^\circ\text{C}$ ;Humidity:90-95%;Times:96h                                                                                                                                                                  | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 5         | 低温<br>COLD RESISTANCE     | 温度:-40℃ $\pm 2^\circ\text{C}$ ;时间:96小时<br>Temp:-40℃ $\pm 2^\circ\text{C}$ ;Times:96h                                                                                                                                                                                         | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 6         | 高温1<br>HEAT RESISTANCE 1  | 温度:100℃ $\pm 2^\circ\text{C}$ ;时间:96小时<br>Temp:100℃ $\pm 2^\circ\text{C}$ ;Times:96h                                                                                                                                                                                         | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 7         | 高温2<br>HEAT RESISTANCE 2  | 温度:155℃ $\pm 2^\circ\text{C}$ ;时间:2小时<br>Temp:155℃ $\pm 2^\circ\text{C}$ ;Times:2h                                                                                                                                                                                           | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 8         | 高温3<br>HEAT RESISTANCE 3  | 温度:85℃ $\pm 2^\circ\text{C}$ ;电压:3.3V/5.0V;时间:96小时<br>Temp:85℃ $\pm 2^\circ\text{C}$ ;Voltage:3.3V/5.0V;Times:96h                                                                                                                                                            | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 9         | 回流焊<br>REFLOW             | 150℃ $\pm 5^\circ\text{C}$ 保持120s后升到270℃ $\pm 5^\circ\text{C}$ 保持10s, 升温 and 保温时间小于200s, 常温放置1~2h后测定<br>Keep 150 °C $\pm$ 5 °C 120s and then rose to 270 °C $\pm$ 5 °C for 10s, warming and holding time is less than the 200s, placed at room temperature 1 ~ 2h after test | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 10        | 盐雾<br>SALT SPRAY          | 盐雾浓度:5%;温度:35℃;时间:24小时<br>Salt density:5%;Temp:35℃;Times:24h                                                                                                                                                                                                                 | 目测无明显腐蚀现象<br>Visual no significant corrosion.               |
| 11        | 老化<br>AGING               | 温度:85℃;时间:30天<br>Temp:85℃;Times:30days                                                                                                                                                                                                                                       | $\Delta FL \leq \pm 5 \text{ppm}$                           |
| 12        | 气密性<br>LEAKAGE            | 氦气(0.6~0.65MPa):10分钟<br>He(0.6~0.65MPa):10min                                                                                                                                                                                                                                | $\leq 3 \times 10^{-9} \text{Pa} \cdot \text{m}^3/\text{s}$ |
| 13        | 焊接<br>SOLDER              | 温度:260℃ $\pm 5^\circ\text{C}$<br>Temp:260℃ $\pm 5^\circ\text{C}$                                                                                                                                                                                                             | 浸锡率大于90%<br>Soldering tin rate greater than 90%             |

### SHENZHEN SCTF ELECTRONICS CO. , LTD

| DATE      | Specification of quartz crystal oscillator<br>石英晶体振荡器规格书 | Page: |
|-----------|----------------------------------------------------------|-------|
| 2022/8/10 | P/N: S7D32.768KB20F30T<br>Spec.NO.: SCTF2020HQ112        | 7     |


## ■ Taping Specifications

UNIT (单位): mm (毫米)



| TEYE    | A   | B   | C   | D    | E   | F   | G   | H   | I   | J   | K   | L   | M    | N    | O     |
|---------|-----|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|-------|
| 5×7 SMD | 0.3 | 7.5 | 1.8 | 16.0 | 7.5 | 5.5 | 8.0 | 4.0 | 2.0 | 1.5 | 2.0 | 4.0 | 13.0 | 60.0 | 180.0 |

## ■ Packaging specifications



SHENZHEN SCTF ELECTRONICS CO. , LTD

| DATE      | Specification of quartz crystal oscillator<br>石英晶体振荡器规格书 | Page: |
|-----------|----------------------------------------------------------|-------|
| 2022/8/10 | P/N: S7D32.768KB20F30T<br>Spec.NO.: SCTF2020HQ112        | 8     |