




REV.	LOCAS.	DESCRIPTION	DATE	DRAWN
01	NEW	BATCH PRODUCTION INITIAL RELEASE.	2009.07.24	車 激
02	△A	依上級要求變更圖號	2011.08.11	李芳忠
03	△A	依業務要求變更無鹵表達方式	2016.03.18	馮國東

Specifications
Current Rating:3.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:600VAC
Contact Resistance:20mΩMax.
Operating Temperature:−40°C to +105°C
Materials
Contact Material:Phosphor Bronze
Insulator Material:High Temperature Thermoplastic, UL 94V-0 Nylon 6T(Halogen Free)△A or the equivalent material
All materials must meet GREENCONN hazardous substances control standards.

Ordering Information

C SHA101 - XX XX A 001 R 1 A X


No. Of Pins Per Row
02~40

Standard Plating
02=Gold Flash
Selective Plating
01=Tin
05=Gold Flash/Tin

Color
1=Black

Standard Packing
A=Box
Selective Packing
C=Tube
E=Cap+Tube
F=Cap+Tape&Reel

Recommended P.C.Board
Layout
(Tolerance:±0.05)



格稜股份有限公司
Greenconn Corporation

GENERAL TOLERANCE		DESIGNED: 馮國東	DATE: 2016.03.18	DWG. NO. △A	TITLE. 2.54 FEMALE HEADER SINGLE ROW DIP TYPE CONNECTOR
X.*±5.0°	X.±0.30	CHECKED: 曹 熙	DATE: 2016.03.18	CSHA101-CA1RA	
.X.*±3.0°	.X.±0.25	CO SIGNED: 劉北平	DATE: 2016.03.18	PART NO.	
.XX.*±2.0°	.XX±0.15	APPROVED: 李 輝	DATE: 2016.03.18	CSHA101-XXXX A001R1AX	
REV. 03	UNIT. mm	SCALE. 4:1	PAGE. 1/1		