




端子材料：镀银紫铜管
 TERMINAL MATERIAL: BRAZEN PLATING TIN



电线范围 Wierange A.W.G.mm ²	型号 ITEM.NO.	尺寸 Dimension.				使用压接工具型号 Using pressing and connecting tool type
		L	D	C	W	
		mm	mm	mm	mm	
2/0A.W.G. 70mm ²	GT70-15	15.0	12.5	11.9	15.8	FXT2000M 使用50钳口 USING50 FOR FXT2000L
	GT70-22	22.0				
	GT70-25	25.0				
	GT70-30	30.0				
3/0A.W.G. 95mm ²	GT90-25	25.0	15.6	14.8	17.3	
	GT90-30	30.0				
	GT90-32	32.0				
	GT90-34	34.0				
4/0A.W.G. 120mm ²	GT120-30	30.0	17.7	16.7	20.2	
	GT120-32	32.0				
	GT120-34	34.0				
	GT120-38	38.0				
150/300A.W.G. 150mm ²	GT120-40	40.0	20.6	19.6	23.0	
	GT150-32	32.0				
	GT150-34	34.0				
	GT150-38	38.0				
150/300A.W.G. 185mm ²	GT150-40	40.0	21.4	20.2	23.9	
	GT185-32	32.0				
	GT185-40	40.0				

管形预绝缘端头
 Pipe bare terminal


端子材料：镀锡紫铜管
 绝缘套材质：尼龙 PVC
 TERMINAL MATERIAL: COPPERTUBE
 INSULATION MATERIAL: NYLON



电线范围 Wierange A.W.G.mm ²	型号 ITEM.NO.	尺寸 Dimension.						法国颜色/德国颜色 COLOR GERMANY COLOR FRANCE	使用压接工具型号 USING PRESSING AND CONNECTING TOOL TYPE
		F	L	W	B	D	C		
22A.W.G. 0.5mm ²	EO0505	5.0	11.0	2.6	6.0	1.3	1.0	□白色 □橙色	使用0.5钳口 USING 0.5 FOR
	EO0506	6.0	12.0						
	EO0508	8.0	14.0						
	EO0510	10.0	16.0						
	EO0512	12.0	18.0						
20A.W.G. 0.75mm ²	E7506	6.0	12.3	2.8	6.3	1.5	1.2	□蓝色 □白色	使用0.75钳口 USING 0.75 FOR
	E7508	8.0	14.3						
	E7510	10.0	16.3						
	E7512	12.0	18.3						
	E7518	18.0	24.3						
18A.W.G. 1.0mm ²	E1006	6.0	12.3	3.0	6.3	1.7	1.4	□红色 □黄色	使用1.0钳口 USING 1.0 FOR
	E1008	8.0	14.3						
	E1010	10.0	16.3						
	E1012	12.0	18.3						
	E1018	18.0	24.3						

管形预绝缘端头
 Pipe bare terminal

端子材料: 镀锡紫铜管
 绝缘套材质: 尼龙 PVC
 TERMINAL MATERIAL: COPPERTUBE
 INSULATION MATERIAL: NYLON



电线范围 Wirerange A.W.G.mm ²	型号 ITEM.NO.	尺寸 Dimension.						法国颜色/德国颜色 COLORGERMANY COLOR FRANCE	使用压接工具型号 USINGPRESSING ANDCONNECTING TOOLTYPE
		F	L	W	B	D	C		
16A.W.G. 1.5mm ²	E1508	8.0	14.3	3.5	6.3	2.0	1.7	☐ 黑色 ☐ 红色	使用1.5钳口 USING1.5FOR
	E1510	10.0	16.3						
	E1512	12.0	18.3	3.5	6.3				
	E1515	15.0	21.3						
	E1518	18..0	24.3						
14A.W.G. 2.5mm ²	E2508	8.0	15.4	4.0	7.4	2.6	2.3	☐ 灰色 ☐ 蓝色	使用2.5钳口 USING2.5FOR
	E2510	10.0	17.4						
	E2512	12.0	19.4						
	E2518	18.0	25.4						
	E2525	25.0	32.4						
12A.W.G. 4.0mm ²	E4009	9.0	16.4	4.5	7.4	3.2	2.8	☐ 橙色 ☐ 灰色	使用4.0钳口 USING4.0FOR
	E4010	10.0	17.4						
	E4012	12.0	19.4						
	E4018	18.0	25.4						
10A.W.G. 4.0mm ²	E6012	12.0	20.5	6.0	8.5	3.9	3.5	☐ 绿色 ☐ 黑色	使用6.0钳口 USING6.0FOR
	E6018	18.0	26.5						
8A.W.G. 10mm ²	E10-12	12.0	20.8	7.5	8.8	4.9	4.5	☐ 棕色 ☐ 乳白色	使用10钳口 USING10FOR
	E10-18	18.0	26.8						
6A.W.G. 16mm ²	E16-12	12.0	22.0	8.7	10.0	6.2	5.8	☐ 乳白色 ☐ 绿色	使用16钳口 USING16FOR
	E16-18	18.0	28.0						
4A.W.G. 25mm ²	E25-12	12.0	24.0	11.0	12.0	7.9	7.5	☐ 黑色 ☐ 棕色	使用25钳口 USING25FOR
	E25-15	15.0	27.0						
	E25-16	16.0	28.0						
	E25-18	18.0	30.0						
	E25-22	22.0	34.0						
2A.W.G. 35mm ²	E35-16	16.0	30.0	12.5	14.0	8.7	8.3	☐ 红色 ☐ 米色	使用35钳口 USING35FOR
	E35-18	18.0	32.0						
	E35-22	22.0	36.0						
	E35-25	25.0	39.0						
1/0A.W.G. 50mm ²	E50-12	12.0	28.0	15.0	16.0	10.9	10.3	☐ 蓝色 ☐ 绿色	使用56钳口 USING56FOR
	E50-20	20.0	36.0						
	E50-25	25.0	41.0						
2/0A.W.G. 70mm ²	E70-20	20.0	37.0	16.0	17.0	14.3	13.5	☐ 黄色	
	E70-25	25.0	42.0						
	E70-27	27.0	44.0						
3/0A.W.G. 95mm ²	E95-25	25.0	44.0	18.5	19.0	15.3	14.5	☐ 红色	
4/0A.W.G. 120mm ²	E120-27	27.0	47.6	20.3	20.6	17.5	16.5	☐ 蓝色	
	E120-32	32.0	52.6						
250/300A.W.G. 150mm ²	E150-25	25.0	50.6	23.4	25.6	20.6	19.6	☐ 黄色	
	E150-27	27.0	52.6						
	E150-32	32.0	57.6						