



P.C. Board Layout
(Tolerance: ± 0.05)

***RoHS Compliant**

9001- 3 7 xx 1 x xx L1 A
 Series 3: 2.54mm 7: Male Position 1: Dip Length 2: Dip Length W1: Dip Length W2: Dip Length
 A: Tray Package
 Blank: W/O Lock
 L1: With Lock
 00: G/F
 10: 10u"
 15: 15u"
 30: 30u"
 C: Dip Tin
 Contact Gold
 G: Dip Tin
 Contact Gold

			X length	1 4.0	2 2.5	W1 13	W2 17
Position	A	B	C	D			
32/16	55.0	49.36	47.40	44.60			
20/10	39.76	34.12	32.16	29.36			
Pitch	Position	Rows with Contacts	Contact Arrange	P/N			
2.54mm	32	a b	 1 2 3 4	9001-3732xCxxL1A			
	16	a -	 1 2 3 4	9001-3716xCxxL1A			
2.54mm	20	a b	 1 2 3 4	9001-3720xCxxL1A			
	10	a -	 1 2 3 4	9001-3710xCxxL1A			

Tolerances	Drawn No.		9001D37011		Title:	9001 Series		1234	
x = ±0.5	Projection					DIN41612 Half			
.x = ±0.25	Unit	mm	Scale	1:1		P/N: 9001-37xx1xxxL1A			
.xx = ±0.15	Drawn By					SHEET 1/1 Ver.No. R2			