



Max.Processing Temp: 180°C for 30–60 seconds
(200°C for 10 seconds)

PM 254 - * - N - Z - * - **

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 2~40Pin	Type Z-直針 H-穿針 S-立貼 VS-頭貼	Length (Plastic) (塑高)	Contact G0:Gold G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold S1:Tin	Plating Flash Gold Gold Gold Gold Gold Gold Flash/Tin
---	------------------------	---------------------------------------	-----------------------------	--	---

			GENERAL TOLERANCE	制 图 DRAWING	 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD				
			DIM TOL	审 核 CHECK					
			X.X ±0.30	批 准 APPROVAL	产品名称 TITLE	2.54单排 排母 直针	版 本 REV.	A	
1	初版发行		X.XX ±0.20	比 例 SCALE	产品料号 PART NO.	PM254-1-N-Z-5.0-XX	单 位 UNITS	mm	
序号 No.	变更内容 MODIFY CONTENT	日 期 MODIFY DATE	X.XXX ±0.10	投 影 Projection	材料 MATERIAL		页 次 SHEET	1/1	
			Angle ±3.0°						



深圳市华灿天禄电子有限公司

ShenzhenhuacantianluELECTRONICS CO.,LTD

产品名称

2 54单排 排母 盲针

版本

A

产品料号

DM254-1-N-7-5 0-VV

单位

mm

材 料

--	--

UNIT 15
页次

1 / 1